## PORTABLE JAW CRUSHERS MP 110C





### **OVERVIEW**

MEKA MP 110C Portable Jaw Crushers are primary crushing units fully assembled on a single trailer frame and mounted on triple-axle bogie. Featuring the highly reliable and productive MP 110 C unit,

coming complete with a hopper, feeder, bypass chute, discharge conveyor, hydraulic control system, electrical control panel, self-cleaning magnet and assisted with hydraulic legs for plant installation.



### **APPLICATIONS**

The MEKA MP 110C is a wheeled jaw crusher unit primarily used in the mining, quarrying, recycling, and demolition industries to break down large, abrasive and hard rocks and other hard materials into smaller, more

manageable pieces. These machines are designed for easy transport and quick setup on-site, making them ideal for remote locations or projects that require frequent relocation.

### WHY MEKA MP 110C?

**Mobility:** Equipped with wheels, MEKA portable jaw crushers can be moved easily from one location to another, reducing the need for permanent installations.

**Versatility:** Suitable for a variety of applications, including mining, quarrying, recycling, and demolition. And also applicable for hard and abrasive rock applications.

**Ease of Use:** Designed for quick setup and simple operation, making them accessible for different levels of users.

**Eco Friendly:** Low emission due to electrical operation, minimizing environmental impact.


**Adjustability:** The Jaw crusher has hydraulic adjustable settings to control the size of the output material.



### HIGHLIGHTS

- Wear resistant feed hopper made of AR400.
- The MEKA MJ 110 C jaw crusher is known for its proven high capacity and reduction capability.
- Single step grizzly feeder with shaft and vibrating drive options.
- Hydraulic crusher setting adjustment.
- Power range capabilities: 400 V 50Hz and 460 V, 60 Hz.
- Under the grizzly chute, all material can be diverted either to the main crusher conveyor or to the by-pass conveyor.

- The heavy-duty under-crusher main conveyor features impact bars located directly under the jaw discharge area.
- Assisted by hydraulic legs for fast and easy set-up.
- Mounted on a chassis with triple-axle bogie and equipped with taillights.
- Self Cleaning Magnet, Electrical Control Panel, Bypass conveyor, Variable frequency drive for the feeder as an option.







### TECHNICAL SPECIFICATIONS

Width 1100 m 43"  Length 6000 mm 19'-8"  Grizzly Length 1400 mm 4'-7"  Grizzly Gap Adjustment 65 mm 2.6"  Motor Power 22 kW 30 HP  Hopper Volume 6.7 m3 / 20 m3 8.8 yd3 / 26.2 yd3  CRUSHER  Model MJ 110C  Feeding Opening 1070 mm x 770 mm 42.1" x 30.3"  Capacity up to 340 mtph 375 stph  CSS Range 75 - 210 mm 3" - 8"  Motor Power 110 kW 150 HP  DISCHARGE CONVEYOR  Model MC 1200X8000P  Belt Width 1200 mm 47"  Length 8000 mm 315"  Motor Power 11 kW 15 HP  BYPASS CONVEYOR  Model MC 650X1850P  Belt Width 650 mm 25.6"  Length 1850 mm 73"  Motor Power 4 kW 5 HP  OVERBELT MAGNETIC SEPARATOR  Model MC 800X1990P  Magnet Dimensions 900x1150 mm 31.5"  Motor Power 2.2kW 3 HP  TRANSPORT DIMENSIONS	MODEL	MP 110C		
Width 1100 m 43"  Length 6000 mm 19'-8"  Grizzly Length 1400 mm 4'-7"  Grizzly Gap Adjustment 65 mm 2.6"  Motor Power 22 kW 30 HP  Hopper Volume 6.7 m3 / 20 m3 8.8 yd3 / 26.2 yd3  CRUSHER  Model MJ 110C  Feeding Opening 1070 mm x 770 mm 42.1" x 30.3"  Capacity up to 340 mtph 375 stph  CSS Range 75 - 210 mm 3" - 8"  Motor Power 110 kW 150 HP  DISCHARGE CONVEYOR  Model MC 1200X8000P  Belt Width 1200 mm 47"  Length 8000 mm 315"  Motor Power 11 kW 15 HP  BYPASS CONVEYOR  Model MC 650X1850P  Belt Width 650 mm 25.6"  Length 1850 mm 73"  Motor Power 4 kW 5 HP  OVERBELT MAGNETIC SEPARATOR  Model MC 800X1990P  Magnet Dimensions 900x1150 mm 31.5"  Motor Power 2.2kW 3 HP  TRANSPORT DIMENSIONS		FEEDER		
Length         6000 mm         19'-8"           Grizzly Length         1400 mm         4'-7"           Grizzly Gap Adjustment         65 mm         2.6"           Motor Power         22 kW         30 HP           Hopper Volume         6.7 m3 / 20 m3         8.8 yd3 / 26.2 yd3           CRUSHER           Model         MJ 110C           Feeding Opening         1070 mm x 770 mm         42.1" x 30.3"           Capacity         up to 340 mtph         375 stph           CSS Range         75 - 210 mm         3" - 8"           Motor Power         110 kW         150 HP           DISCHARGE CONVEYOR           Model         MC 1200X8000P           Belt Width         1200 mm         47"           Length         8000 mm         315"           Motor Power         11 kW         15 HP           BYPASS CONVEYOR           Model         MC 650X1850P           Belt Width         650 mm         25.6"           Length         1850 mm         73"           Motor Power         4 kW         5 HP           OVERBELT MAGNETIC SEPARATOR           Model         MC 800X1990P           M	Model	MGF 1160		
Grizzly Length         1400 mm         4'-7"           Grizzly Gap Adjustment         65 mm         2.6"           Motor Power         22 kW         30 HP           Hopper Volume         6.7 m3 / 20 m3         8.8 yd3 / 26.2 yd3           CRUSHER           Model         MJ 110C           Feeding Opening         1070 mm x 770 mm         42.1" x 30.3"           Capacity         up to 340 mtph         375 stph           CSS Range         75 - 210 mm         3" - 8"           Motor Power         110 kW         150 HP           DISCHARGE CONVEYOR           Model         MC 1200X8000P           Belt Width         1200 mm         47"           Length         8000 mm         315"           Model         MC 650X1850P           Belt Width         650 mm         25.6"           Length         1850 mm         73"           Motor Power         4 kW         5 HP           OVERBELT MAGNETIC SEPARATOR           Model         MC 800X1990P           Magnet Dimensions         900X1150 mm         35.4" x 45.3"           Belt Width         800 mm         31.5"           Length	Width	1100 m	43"	
Grizzly Gap Adjustment         65 mm         2.6"           Motor Power         22 kW         30 HP           Hopper Volume         6.7 m3 / 20 m3         8.8 yd3 / 26.2 yd3           CRUSHER           Model         MJ 110C           Feeding Opening         1070 mm x 770 mm         42.1" x 30.3"           Capacity         up to 340 mtph         375 stph           CSS Range         75 - 210 mm         3" - 8"           Motor Power         110 kW         150 HP           DISCHARGE CONVEYOR           Model         MC 1200X8000P           Belt Width         1200 mm         47"           Length         8000 mm         315"           Motor Power         11 kW         15 HP           Belt Width         650 mm         25.6"           Length         1850 mm         73"           Motor Power         4 kW         5 HP           OVERBELT MAGNETIC SEPARATOR           Model         MC 800X1990P           Magnet Dimensions         900x1150 mm         35.4" x 45.3"           Belt Width         800 mm         31.5"           Length         1990 mm         78.3"           Motor Power	Length	6000 mm	19'-8"	
Motor Power         22 kW         30 HP           Hopper Volume         6.7 m3 / 20 m3         8.8 yd3 / 26.2 yd3           CRUSHER           Model         MJ 110C           Feeding Opening         1070 mm x 770 mm         42.1" x 30.3"           Capacity         up to 340 mtph         375 stph           CSS Range         75 - 210 mm         3" - 8"           Motor Power         110 kW         150 HP           DISCHARGE CONVEYOR           Model         MC 1200 x8000P           Belt Width         1200 mm         47"           Length         8000 mm         315"           Motor Power         11 kW         15 HP           Belt Width         650 mm         25.6"           Length         1850 mm         73"           Motor Power         4 kW         5 HP           OVERBELT MAGNETIC SEPARATOR           Model         MC 800X1990P           Magnet Dimensions         900x1150 mm         35.4" x 45.3"           Belt Width         800 mm         31.5"           Length         1990 mm         78.3"           Motor Power         2.2kW         3 HP	Grizzly Length	1400 mm	4'-7"	
Hopper Volume	Grizzly Gap Adjustment	65 mm	2.6"	
CRUSHER           Model         MJ 110C           Feeding Opening         1070 mm x 770 mm         42.1" x 30.3"           Capacity         up to 340 mtph         375 stph           CSS Range         75 - 210 mm         3" - 8"           Motor Power         110 kW         150 HP           DISCHARGE CONVEYOR           Model         MC 1200X8000P           Bett Width         1200 mm         47"           Length         8000 mm         315"           Motor Power         11 kW         15 HP           ByPASS CONVEYOR           Model         MC 650X1850P           Bett Width         650 mm         25.6"           Length         1850 mm         73"           Motor Power         4 kW         5 HP           OVERBELT MAGNETIC SEPARATOR           Model         MC 800X1990P           Magnet Dimensions         900x1150 mm         35.4" x 45.3"           Belt Width         800 mm         31.5"           Length         1990 mm         78.3"           Motor Power         2.2kW         3 HP           TRANSPORT DIMENSIONS	Motor Power	22 kW	30 HP	
Model         MJ 110C           Feeding Opening         1070 mm x 770 mm         42.1" x 30.3"           Capacity         up to 340 mtph         375 stph           CSS Range         75 - 210 mm         3" - 8"           Motor Power         110 kW         150 HP           DISCHARGE CONVEYOR           Model         MC 1200X8000P           Belt Width         1200 mm         47"           Length         8000 mm         315"           Motor Power         11 kW         15 HP           Belt Width         650 mm         25.6"           Length         1850 mm         73"           Motor Power         4 kW         5 HP           OVERBELT MAGNETIC SEPARATOR           Model         MC 800X1990P           Magnet Dimensions         900x1150 mm         35.4" x 45.3"           Belt Width         800 mm         31.5"           Length         1990 mm         78.3"           Motor Power         2.2kW         3 HP	Hopper Volume	6.7 m3 / 20 m3	8.8 yd3 / 26.2 yd3	
Teeding Opening		CRUSHER		
Capacity         up to 340 mtph         375 stph           CSS Range         75 - 210 mm         3" - 8"           Motor Power         110 kW         150 HP           DISCHARGE CONVEYOR           Model         MC 1200X8000P           Belt Width         1200 mm         47"           Length         8000 mm         315"           Motor Power         11 kW         15 HP           BYPASS CONVEYOR           Model         MC 650X1850P           Belt Width         650 mm         25.6"           Length         1850 mm         73"           Motor Power         4 kW         5 HP           OVERBELT MAGNETIC SEPARATOR           Model         MC 800X1990P           Magnet Dimensions         900x1150 mm         35.4" x 45.3"           Belt Width         800 mm         31.5"           Length         1990 mm         78.3"           Motor Power         2.2kW         3 HP           TRANSPORT DIMENSIONS	Model	MJ 110C		
CSS Range         75 - 210 mm         3" - 8"           Motor Power         110 kW         150 HP           DISCHARGE CONVEYOR           Model         MC 1200 X8000P           Belt Width         1200 mm         47"           Length         8000 mm         315"           Motor Power         11 kW         15 HP           BYPASS CONVEYOR           Model         MC 650 X1850P           Belt Width         650 mm         25.6"           Length         1850 mm         73"           Motor Power         4 kW         5 HP           OVERBELT MAGNETIC SEPARATOR           Model         MC 800X1990P           Magnet Dimensions         900x1150 mm         35.4" x 45.3"           Belt Width         800 mm         31.5"           Length         1990 mm         78.3"           Motor Power         2.2kW         3 HP           TRANSPORT DIMENSIONS	Feeding Opening	1070 mm x 770 mm	42.1" x 30.3"	
Motor Power	Capacity	up to 340 mtph	375 stph	
Model	CSS Range	75 - 210 mm	3" - 8"	
Model         MC 1200X8000P           Belt Width         1200 mm         47"           Length         8000 mm         315"           Motor Power         11 kW         15 HP           BYPASS CONVEYOR           Model         MC 650X1850P           Belt Width         650 mm         25.6"           Length         1850 mm         73"           Motor Power         4 kW         5 HP           OVERBELT MAGNETIC SEPARATOR           Model         MC 800X1990P           Magnet Dimensions         900x1150 mm         35.4" x 45.3"           Belt Width         800 mm         31.5"           Length         1990 mm         78.3"           Motor Power         2.2kW         3 HP           TRANSPORT DIMENSIONS	Motor Power	110 kW	150 HP	
Belt Width       1200 mm       47"         Length       8000 mm       315"         Motor Power       11 kW       15 HP         BYPASS CONVEYOR         Model       MC 650X1850P         Belt Width       650 mm       25.6"         Length       1850 mm       73"         Motor Power       4 kW       5 HP         OVERBELT MAGNETIC SEPARATOR         Model       MC 800X1990P         Magnet Dimensions       900x1150 mm       35.4" x 45.3"         Belt Width       800 mm       31.5"         Length       1990 mm       78.3"         Motor Power       2.2kW       3 HP         TRANSPORT DIMENSIONS		DISCHARGE CONVEYOR		
Length         8000 mm         315"           Motor Power         11 kW         15 HP           BYPASS CONVEYOR           Model         MC 650X1850P           Belt Width         650 mm         25.6"           Length         1850 mm         73"           Motor Power         4 kW         5 HP           OVERBELT MAGNETIC SEPARATOR           Model         MC 800X1990P           Magnet Dimensions         900x1150 mm         35.4" x 45.3"           Belt Width         800 mm         31.5"           Length         1990 mm         78.3"           Motor Power         2.2kW         3 HP           TRANSPORT DIMENSIONS	Model	MC 1200X8000P		
Motor Power         11 kW         15 HP           BYPASS CONVEYOR           Model         MC 650X1850P           Belt Width         650 mm         25.6"           Length         1850 mm         73"           Motor Power         4 kW         5 HP           OVERBELT MAGNETIC SEPARATOR           Model         MC 800X1990P           Magnet Dimensions         900x1150 mm         35.4" x 45.3"           Belt Width         800 mm         31.5"           Length         1990 mm         78.3"           Motor Power         2.2kW         3 HP           TRANSPORT DIMENSIONS	Belt Width	1200 mm	47"	
Model         MC 650X1850P           Belt Width         650 mm         25.6"           Length         1850 mm         73"           Motor Power         4 kW         5 HP           OVERBELT MAGNETIC SEPARATOR           Model         MC 800X1990P           Magnet Dimensions         900x1150 mm         35.4" x 45.3"           Belt Width         800 mm         31.5"           Length         1990 mm         78.3"           Motor Power         2.2kW         3 HP           TRANSPORT DIMENSIONS	Length	8000 mm	315"	
Model         MC 650X1850P           Belt Width         650 mm         25.6"           Length         1850 mm         73"           Motor Power         4 kW         5 HP           OVERBELT MAGNETIC SEPARATOR           Model         MC 800X1990P           Magnet Dimensions         900x1150 mm         35.4" x 45.3"           Belt Width         800 mm         31.5"           Length         1990 mm         78.3"           Motor Power         2.2kW         3 HP           TRANSPORT DIMENSIONS	Motor Power	11 kW	15 HP	
Belt Width         650 mm         25.6"           Length         1850 mm         73"           Motor Power         4 kW         5 HP           OVERBELT MAGNETIC SEPARATOR           Model         MC 800X1990P           Magnet Dimensions         900x1150 mm         35.4" x 45.3"           Belt Width         800 mm         31.5"           Length         1990 mm         78.3"           Motor Power         2.2kW         3 HP           TRANSPORT DIMENSIONS		BYPASS CONVEYOR		
Length       1850 mm       73"         Motor Power       4 kW       5 HP         OVERBELT MAGNETIC SEPARATOR         Model       MC 800X1990P         Magnet Dimensions       900x1150 mm       35.4" x 45.3"         Belt Width       800 mm       31.5"         Length       1990 mm       78.3"         Motor Power       2.2kW       3 HP         TRANSPORT DIMENSIONS	Model	MC 650X1850P		
Motor Power         4 kW         5 HP           OVERBELT MAGNETIC SEPARATOR           Model         MC 800X1990P           Magnet Dimensions         900x1150 mm         35.4" x 45.3"           Belt Width         800 mm         31.5"           Length         1990 mm         78.3"           Motor Power         2.2kW         3 HP           TRANSPORT DIMENSIONS	Belt Width	650 mm	25.6"	
OVERBELT MAGNETIC SEPARATOR           Model         MC 800X1990P           Magnet Dimensions         900x1150 mm         35.4" x 45.3"           Belt Width         800 mm         31.5"           Length         1990 mm         78.3"           Motor Power         2.2kW         3 HP           TRANSPORT DIMENSIONS	Length	1850 mm	73"	
Model         MC 800X1990P           Magnet Dimensions         900x1150 mm         35.4" x 45.3"           Belt Width         800 mm         31.5"           Length         1990 mm         78.3"           Motor Power         2.2kW         3 HP           TRANSPORT DIMENSIONS	Motor Power	4 kW	5 HP	
Magnet Dimensions         900x1150 mm         35.4" x 45.3"           Belt Width         800 mm         31.5"           Length         1990 mm         78.3"           Motor Power         2.2kW         3 HP           TRANSPORT DIMENSIONS		OVERBELT MAGNETIC SEPARAT	OR	
Belt Width         800 mm         31.5"           Length         1990 mm         78.3"           Motor Power         2.2kW         3 HP           TRANSPORT DIMENSIONS	Model	MC 800	MC 800X1990P	
Length         1990 mm         78.3"           Motor Power         2.2kW         3 HP           TRANSPORT DIMENSIONS	Magnet Dimensions	900x1150 mm	35.4" x 45.3"	
Motor Power 2.2kW 3 HP TRANSPORT DIMENSIONS	Belt Width	800 mm	31.5"	
TRANSPORT DIMENSIONS	Length	1990 mm	78.3"	
	Motor Power	2.2kW	3 HP	
Length 16210 mm 53'-2"		TRANSPORT DIMENSIONS		
	Length	16210 mm	53'-2"	
<b>Width</b> 2970 mm 9'-9"	Width	2970 mm	9'-9"	
Height 4150 mm 13'-7"	Height	4150 mm	13'-7"	
<b>Weight</b> 52000 kg 114640 lbs	Weight	52000 kg	114640 lbs	
OPERATING DIMENSIONS				
<b>Length</b> 16210 mm 53'-2"	Length	16210 mm	53'-2"	
Width 4190 mm 13'-9"	Width	4190 mm	13'-9"	
<b>Height</b> 4720 mm 15'-6"	Height	4720 mm	15'-6"	

### STANDARD DIMENSIONS AND TECHNICAL SPECIFICATIONS

# OPERATING DIMENSIONS (6210 [53-27] 254 [87-7] 2696 [13-0 1/27] 12003 [39-5 1/27] 12000 [41-87]

## TRANSPORT DIMENSIONS & LOADS 16210 [53:27] 16210 [53:27] 12023 [39:5 1/27] 29530 kg (65101 lbs) 9843 kg (21700 lbs) per axie

### THE CHOICE OF PROFESSIONALS IN MORE THAN 100 COUNTRIES: MEKA

MEKA has a global capacity with more than 80 engineers, nearly 500 employees and experience of producing more than 4000 complete plants. With 5 separate production facilities and a worldwide service network, it is a reliable manufacturer.

With its after-sales service network and strong infrastructure in spare parts, MEKA does not only produce equipment or plants, but also offers you the comfort of predictable production and uninterrupted earnings.



